

Index

Index entries for Exim variables such as *\$local_part*, command line options such as `-bp`, and other configuration items that start with a non-alphabetic character (such as `+include_unknown` and `:include:`) are sorted without their leading special character. All options are indexed directly under their own names, but string expansion operators are placed under *expansion*. I have not indexed the appendix because the expansion items and variables appear there in alphabetical order.

Numbers

- \$0*, *\$1*, *\$2*, etc. variables 380
 - after matches in filters 232
 - in rewriting rules 379
- 0.0.0.0 (IP address)
 - ignoring in routers 109
- 127.0.0.1 (IP address) 62, 250
 - ignoring in routers 109
 - in default configuration 315
 - use by SpamAssassin 361
 - use in DNS blacklists 335
- 8-bit bytes 467–468
 - encoding not done 467
 - in log lines 517
 - in message body 301
 - in user names 371
- 8BITMIME 468

Symbols

- () (parentheses)
 - in Exim filters 219
 - in filter condition 229
 - in header lines 10
 - round host names in log lines 307, 518
- ! (exclamation mark)
 - at start of local part 454
 - for negation in lists 39, 59, 441, 442
 - for negation of named list 59
 - in ACLs 323
 - in bang-path addressing 384
 - in expansion conditions 421
 - in local parts 313
- " (double-quote)
 - in Exim filters 219
 - in option settings 53
 - in *pipe* filter command 224
 - in **pipe** transport 198
- " (double-quote) (*continued*)
 - in redirection to pipe 142
 - in substring for extraction 433
- # (hash, sharp sign)
 - in alias files 391
 - in configuration file 51
 - in ETRN commands 297
 - in Exim filters 218
 - in interpolated lists 442
 - in *Local/Makefile* 543
- \$ (dollar)
 - as string expansion trigger 39
 - in Exim filters 219
 - in expanded strings 407
- % (percent)
 - in addresses 384
 - in local parts 313
 - in quota threshold 195
 - “percent hack” 384
- & (ampersand) in “gecos” fields 370
- ' (single-quote)
 - in *pipe* filter command 224
 - in **pipe** transport 198
 - in redirection to pipe 142
- * (asterisk)
 - ** in log lines 517
 - *> in log lines 502
 - *@ in single-key lookup types 396, 397
 - as host list item 448
 - in authenticated ACL condition 337
 - in domain lists 445
 - in encrypted ACL condition 336
 - in host lists 451
 - in partial match keys 396, 397
 - in retry rules 262, 264
 - in rewriting pattern 379
 - in rewriting replacement string 380
 - in *route_list* option 89

- * (asterisk) (*continued*)
 - in search type 76
 - in single-key lookup types 396, 397
 - in wild linear searches 392
- + (plus)
 - for referencing named lists 443
 - in named lists 59
 - in `require_files` lists 106
- , (comma)
 - in header insertions 409
 - in redirection list 140
 - in redirection pipe command 142
- (hyphen)
 - > in log lines 520
 - option 502
- . (dot)
 - as message terminator 15, 482
 - at end of domain 469
 - in local part 314, 468
 - in phrase part of address 468
- / (forward slash)
 - in local parts 313
 - in redirection item 142
- : (colon)
 - ::1 (IPv6 address) 250
 - alone in a list 313, 453
 - as list separator 58, 440
 - in expanded strings 409
 - in `lsearch` files 391
 - including in lists 58
- ; (semicolon)
 - in address lists 454
 - in domain lists 446
 - in host lists 449
 - in **manualroute** route list 130
 - in retry rules 266
- < (left angle bracket)
 - <= in log lines 517
 - changing list separator 59, 440
- <> (angle brackets)
 - empty envelope sender 13
 - excess in address 469
 - in AUTH parameters 287
 - in Exim monitor display 532
 - in `exim_checkaccess` utility 536
 - in log lines 519
 - in *Return-path*: header line 43, 155
 - in SMTP commands 469
 - with `-f` option 485
- <> (angle brackets) (*continued*)
 - with `-Mes` option 494
- = (equals)
 - => in log lines 517
 - == in log lines 517
- > (right angle bracket)
 - in list of local parts 453
- @ (at sign)
 - @@ in address lists 453–454
 - @[] in domain lists 307, 445
 - @[] in host lists 448
 - in domain lists 307, 445
 - in email addresses 10
 - in local parts 313
 - in lookup defaults 77
- [] (square brackets)
 - in domain literal addresses 469
- \ (backslash)
 - \N in regular expressions 231, 407
 - \N in rewriting rules 380
 - as continuation character 51
 - in `echo` command 288
 - in Exim filters 219
 - in expanded strings 407
 - in message ACL modifiers 328
 - in `perl_startup` option 437
 - in **pipe** transport command 198, 224
 - in printed data quoting 416
 - in quoted strings 53, 149
 - in redirection list 141
 - in regular expressions 231
 - in rewriting patterns 379
 - in SQL lookup data 403
- ^ (circumflex)
 - in address lists 453
 - in domain lists 446
 - in host lists 452
 - in **plaintext** client configuration 293
 - in wild linear searches 392
- _ (underscore)
 - in authenticator mechanism names 289
 - in host names 308
 - in macro names 54
- { } (curly brackets, braces)
 - in encrypted strings 423
 - in expanded strings 407, 409
- | (vertical bar)
 - in local parts 313
 - in redirection items 142

A

- A (DNS IPv4 address record) 20
- A= in log lines 519
- AAAA (DNS IPv6 address record) 20
- abuse of sender address 18
- accept** router 41, 122–123
 - specifying transports for 123
- accept verb in ACLs 321
- accept_8bitmime option 468
- accounts
 - checking in routers 105
 - large number of 203
 - multiple 233
- ACL (Access Control List) 312–345
 - authentication, checking for 336
 - case-sensitivity in local parts 329
 - certificate, checking for verified 336
 - client SMTP authorization 344–345, 405
 - conditions 332–345
 - custom checks 341
 - DNS black lists 333–336
 - EHLO, checking for verified 337
 - encryption, checking for 336
 - finding ACLs 319
 - format of ACLs 321
 - header line checking 340–341
 - host checking 332–333
 - in default configuration 312–316
 - inline ACLs 319
 - modifiers 324–331
 - MX backup, detecting 339
 - negation of conditions 323
 - nested ACLs 345
 - rate limiting 342–344
 - RCPT vs DATA 316
 - reading from file 319
 - recipient address, checking 339
 - restricting DNS lists by data received 335
 - return codes from 319
 - sender address, testing for 337–338
 - sender address, verifying 338–339
 - specifying local submission 330
 - specifying when to use 316–319
 - unset options 319
 - variables set in message ACLs 320
 - variables set in non-message ACLs 320
 - variables, settable in ACLs 322–323
 - verbs 321–322
- acl ACL condition 345
- acl_not_smtp_mime option 362
- acl_smtp_mime option 362
- acl_smtp_xxx options 317
- \$acl_verify_message* variable 328
- add filter command 221–222
- address (*see also* IP address)
 - batching in local transports 174–176
 - canonicizing not done 470
 - domain literal 469–470
 - duplicate 44, 140
 - in header lines, qualifying 302
 - invalid characters in 21
 - multiple for one user 86–88
 - multiple in **smtp** transport 166
 - processing 35–37
 - processing after redirection 107
 - redirecting to the same 140
 - redirection 137–150
 - rewriting *see* rewriting addresses
 - routing 35–37
 - source routed 470
 - syntax extensions 468–469
 - syntax, RFC 2822 vs RFC 2821 9
 - unqualified from remote host 305–306
 - unrouteable, message for 116
 - variations in format 10
 - verification *see* verifying addresses
- address lists (*see also* lists) 58, 452–455
 - case of letters in 455
 - in rewriting rules 379
 - local part list per domain 453–454
 - regular expressions in 453
- address_data option 91, 110–111
- \$address_data* variable 91, 110–111
 - set by **queryprogram** router 136
- add_header ACL modifier 324
- admin users 465–466, 488, 500
- administering Exim 505–540
- admin_groups option 465
- aliasing
 - including domains when 76, 138
 - interaction with forwarding 141
 - local parts without domains 76
 - maintaining files 536
 - several domains in one file 138
 - simple example 39
- allow_commands option 201
- allow_defer option 143
- allow_domain_literals option 470

- allow_fail option 83, 143, 235
- allow_fifo option 183
- allow_filter option 212
- allow_freeze option 235
- allow_localhost option 174
- allow_mx_to_ip option 471
- allow_symlink option 183
- all_parents log selector 148
- ampersand *see* & (ampersand)
- ancestor checking in **redirect** router 145
- angle brackets *see* <> (angle brackets)
- appendfile** transport 43, 180–196
 - affixes in RCPT for BSMTP 157
 - batching addresses in 174–176
 - checking mailbox format 186
 - configuring for use with Sieve 184
 - delivering to separate files 190–192
 - file owner and mode 184
 - lock files 187–188
 - locking a mailbox 187–190
 - locking functions 188
 - MBX format 185
 - non-existent file, creating 183
 - options for mailbox locking 189–190
 - options in common with **pipe** 176–180
 - quotas for mailboxes 192–196
 - single-file, specifying 181
- arithmetic, in expansion strings 416
- asterisk *see* * (asterisk)
- at sign *see* @ (at sign)
- attachments 10
 - detecting unwanted 364
 - removing 98
- AUTH parameter for MAIL command 287, 289
- AUTH SMTP command 282
 - refusing when not encrypted 341
- \$auth1*, *\$auth2*, etc. variables
 - in **cram_md5** authenticator 293
 - in **plaintext** authenticator 290
- authenticated ACL condition 336
- authenticated sender for local message 289
- \$authenticated_id* variable 294
- authenticated_sender option 171
- \$authenticated_sender* variable 287
 - in ACLs 320
- authenticated_sender_force
 - option 171
- authentication 281–295
 - advertising 285
 - authentication (*continued*)
 - by an Exim client 288–289
 - choice of mechanism 285–286
 - CRAM-MD5 client configuration 294
 - CRAM-MD5 description 284–285
 - CRAM-MD5 server configuration 293
 - Cyrus SASL 295
 - Dovecot 295
 - Exim authenticators 286–295
 - in encrypted connections only 285
 - in **smtp** transport 170
 - Kerberos 295
 - LOGIN client configuration 293
 - LOGIN description 283–284
 - LOGIN server configuration 291
 - mechanisms 283–285
 - of SMTP connections 16
 - on an Exim server 287–288
 - options for all authenticators 289–290
 - overview 282
 - password checking for **plaintext** 292–293
 - PLAIN client configuration 293
 - PLAIN description 283
 - PLAIN server configuration 291
 - SPA (NTLM) 295
 - testing server 288
 - auth_advertise_hosts option 285
 - Auto-Submitted*: header line 476
 - automatic replies 204–207
 - automount 181
 - autoreply messages
 - creating in filters 225–228
 - logging 228
 - specifying once-only 227
 - autoreply** transport 204–207
 - compared with **pipe** 204
 - message parameters 205–206
 - once-only messages 207
 - recipients, not sending to 207
 - use of header-changing options 205
 - with empty sender 205

B

- backslash *see* \ (backslash)
- backup host 8
 - after authentication failure 289
 - fallback not used 116
 - for LDAP 399

- backup host (*continued*)
 - MX backup 125, 310
 - MX, detecting in ACLs 339
 - bang-path addressing
 - not supported 90
 - rewriting 384
 - base 62 encoding 49
 - base 64 encoding 288
 - batch delivery
 - conditions for 175
 - \$domain* variable 175
 - \$local_part* variable 175
 - batched SMTP *see* BSMTP (Batched SMTP)
 - batching addresses
 - in local transports 174–176
 - batch_id option 175
 - batch_max option 95, 132, 175, 179
 - in **lmtp** transport 204
 - BATV 352–356
 - Bcc:** header line 12
 - input processing 373
 - with **-t** 303, 483
 - bcc** option 205
 - bd** option 246, 481
 - be** option 438
 - begin in configuration file 52
 - begins filter condition 230
 - bem** option 439
 - Berkeley DB 393
 - Berkeley mailbox format 176
 - bf...** options 216–217
 - bh** option 288, 497, 535
 - bhc** option 497
 - bi** option 503
 - binary distribution 3
 - bi_command** option 503
 - black lists 19, 333–336
 - :blackhole:** in redirection lists 143
 - blocking
 - hosts 332
 - messages 19
 - bm** option 482
 - body of message
 - definition 10
 - modifying 98–99
 - BODY SMTP parameter 468
 - body_only** option 154
 - Boolean option values 53
 - Bounce address tag validation 352–356
 - bounce message 46, 474–475
 - autoreply** transport 204
 - copying 474
 - customizing 476–478
 - frozen 60
 - reply address for 474
 - size of, controlling 154, 301
 - verifiable sender in header lines 341
 - \$bounced_recipient* variable 477
 - bounce_message_file** option 477
 - bounce_message_text** option 476
 - bP** option 56, 495
 - hidden data 401
 - bp** option 50, 465
 - bp...** options 492
 - brace *see* { } (curly brackets, braces)
 - brt** option 499
 - bs** option 299, 302, 303, 482
 - bs** option 295, 298, 302, 303, 482
 - BSMTP (Batched SMTP) 95, 178, 482, 179–180, 299
 - for incoming message 303
 - including HELO 179
 - input error details 299
 - use of affixes 157
 - bt** option 496
 - build directory 550
 - building Exim 541–550
 - configuration for 543–550
 - driver choices 545
 - fetching and unpacking 542–543
 - for multiple systems 549–550
 - mandatory settings 545
 - minimal configuration 547
 - module choices 545
 - monitor configuration 548
 - optional settings 548
 - prerequisites 541
 - recommended settings 546
 - system-related settings 547
 - bv** and **-bvs** options 352, 496
 - bV** option 495
 - bydns in **route_list** 129
 - bypassing **.forward** files 101, 149
- ## C
- C compiler 541, 547
 - C=** in log lines 515

- C option 491
- c-client 185
- caching
 - black list lookups 335
 - callout information 350
 - in DNS 22, 68
 - lookup data 406
 - named list matches 443
 - sender address verification 339
- callout
 - caching 350
 - for address verification 346–350
 - testing 497
- callout verification option 346
- carriage return *see* CR (carriage return)
- case of letters, forcing 413
- case-sensitivity
 - in address lists 455
 - in authenticator public names 289
 - in domain names 21
 - in filter conditions 230
 - in local parts 92–93
 - in local parts in ACLs 329
 - of postmaster address 27
- +caseful in address lists 455
- caseful_local_part control 329
- caseful_local_part option 92
 - in **redirect** router 138
- caselower_local_part control 329
- Cc: header line 11
 - with -t 303, 483
- cc option 205
- cdb (Constant Data Base) 75
 - files 394–395
- cdb lookup type 394–395
- central process, lack of 30
- certificate
 - requesting from client 279
 - self-signed, creating 277
 - verified 336
- characters
 - 8-bit bytes 301, 467–468
 - 8-bit bytes in log lines 517
 - 8-bit bytes in user names 371
 - printing 416
 - translating 419
- checking
 - file attributes in **redirect** 145
 - incoming mail 17–20
- check_ancestor option 146
- check_group option
 - appendfile** transport 184
 - redirect** router 145
- check_local_user option 40, 105, 114, 122, 152, 153, 263
 - for file owner in **redirect** router 145
- check_log_inodes option 472
- check_log_space option 472
- check_owner option
 - appendfile** transport 184, 460
 - redirect** router 145
- check_secondary_mx option 125
- check_spool_inodes option 472
- check_spool_space option 63, 296, 472
- check_string option 178
 - with BSMTP 180
 - with directory option 191
- child addresses
 - ancestor checking 145
 - hiding in error messages 139
 - interaction with *\$address_data* variable 110
 - processing 107
 - rewriting 148
- circumflex *see* ^ (circumflex)
- client, non-queueing 461–462
- client SMTP authorization (CSA)
 - 344–345, 405
- client_name option 294
- client_secret option 294
- client_send option 293
- closed mailing lists 81–83
- CNAME (DNS “canonical name” record)
 - 25, 470
- collateral spam 18, 476
- colon *see* : (colon)
- comma *see* , (comma)
- command
 - for -bi option 503
 - for ETRN 298
 - for **pipe** transport 196–197
 - for transport filter 160
- command line
 - adding data to a message 484–486
 - compatibility with Sendmail 502–503
 - configuration overrides 491
 - debugging 500–502
 - delivery control 486–487
 - error routing (non-SMTP message) 487

- command line (*continued*)
 - input mode control 481–484
 - interface 2, 480–504
 - macro overrides 492
 - message control 493–494
 - option termination 502
 - option types 480–481
 - options *see individual options*
 - Perl options 437
 - queue information 492
 - suppressing delivery 500
 - testing options 495–500
- command option
 - pipe** transport 197
 - queryprogram** router 135
- command_group option 135
- command_timeout option 170
- command_user option 135
- comments
 - in Exim filters 218
 - in header lines 10
 - in interpolated lists 442
 - in *Local/Makefile* 543
 - in rewritten header lines 382
 - in runtime configuration 51
- condition ACL condition 341
- condition option 95, 107
- configuration
 - auxiliary data 32
 - comment lines 51
 - conditional parts of 56
 - for large installations 66–70
 - general description 51–52
 - hiding data 56
 - including other files 54
 - layout of file 51–52
 - line continuation 51
 - macros 54–55
 - minimal example 52
 - overriding on command line 491
 - overview 31–33
 - rewrite section 376
 - sections, definition 51
 - testing 495–500
 - updating 249, 536
 - whitespace at line continuation 51
- connection
 - encrypted 276–281
 - error response 258
- connection (*continued*)
 - loss of 258
 - refusal by remote host 258
 - reusing 167
 - timeout 258
- connection_max_messages option 168
- connect_timeout option 169
- contains filter condition 231
- content scanning
 - at SMTP time 357–367
 - of accepted messages 93–98
- Content-Type*: Header line 12
- continuation lines
 - in alias files 39
 - in header 10
 - in runtime configuration 51
- control ACL modifier 325, 329–331
- copying messages 108
- CR (carriage return) 9, 301, 471, 484
 - in local delivery 179
- cram_md5** authenticator
 - in a client 294–295
 - in a server 293–294
- create_directory option 184, 191
- create_file option 183
- cron*
 - cycling log files 507
 - output from 302
 - starting queue runners 30, 252, 488
 - tidying Exim databases 539
- crypt()* function 423
- crypteq expansion item 292
- CSA (client SMTP authorization)
 - 344–345, 405
- curly bracket *see* { } (curly brackets, braces)
- current directory
 - in transports 152
 - set in router for transport 115
- current_directory option
 - queryprogram** router 135
 - transports 152
- customizing bounce messages 476–478
- customizing warning messages 478
- CV= in log lines 516
- cycling log files 507–508
- Cyrus
 - IMAP server 171, 203
 - pwcheck* daemon 425
 - SASL library, authenticator for 295

- Cyrus (*continued*)
saslauthd daemon 425
- D**
- D file 239, 250
 - D option 55, 492
 - d option 500
 - daemon 295
 - checks on connections 248–249
 - controlling terminal for 246
 - interfaces 246
 - killing 246
 - on an intermittently connected host 274
 - ports 247
 - process description 246–250
 - process number 51
 - restarting 32, 249
 - SIGHUP signal 249
 - starting 481
 - starting queue runners 65
 - testing 553
 - timer for queue runners 249
 - uses for 30
 - daemon_smtp_ports* option 247
 - data option 79, 137
 - data shared by Exim processes 238–244
 - DATA SMTP command 15
 - error response to 259
 - database lookup *see* lookup
 - database queries, reducing number of 431
 - data_timeout* option 170
 - Date*: header line 12
 - input processing 373
 - datestamped log files 508
 - db* directory 242
 - DBM files 242, 393–394
 - definition 72
 - in domain list 72
 - maintaining 536–537
 - terminating zero in key 394
 - DBM library, required for building 541
 - dbm lookup type 393–394
 - debugging 500–502
 - routers 120
 - selector summary 501
 - transports 153
 - debug_print* option
 - in routers 120, 500
 - debug_print* option (*continued*)
 - in transports 153, 500
 - decline (router outcome) definition 36
 - defer (router outcome)
 - definition 37
 - forcing 143–144
 - :defer: in redirection lists 143
 - defer verb in ACLs 321
 - defer_ok* callout parameter 347
 - defer_ok* verification option 346
 - +*defer_unknown* in DNS black lists 334
 - defunct processes 249
 - delay
 - minimizing in name server 68
 - warning message 475–476
 - delay ACL modifier 325
 - delay_after_cutoff* option 174, 270
 - delay_warning* option 475
 - delay_warning_condition* option 475
 - deliver* filter command 222–223
 - delivered filter condition 234
 - delivery
 - as *root* considered harmful 459
 - asynchronous and synchronous 486
 - batched SMTP 179–180
 - command line control options 486
 - complications 45–46
 - delay warning message 475–476
 - escaping lines 178
 - external agent 85–86
 - failure report *see* bounce message
 - finding when next 525
 - forcing 493
 - ignoring local part 90–92
 - limiting number of processes 65
 - line terminators 179
 - local, with special group 152
 - message separators 176–178
 - one file per message 190–192
 - overview 33–34
 - parallel, limiting 64, 254
 - real time taken 513
 - retry rules for local 263–264
 - retry rules for remote 263
 - setting environment in routers 113–115
 - simultaneous 67
 - suppressing 500
 - suspending at high system load 61
 - to a specific domain 490

- delivery (*continued*)
 - to file or pipe 47
- delivery errors 257–275
 - host errors 258–259
 - local deliveries 261
 - long-term failures 269–270
 - message errors 259
 - problems of classification 260–261
 - recipient errors 259–260
 - types of 258–261
 - ultimate address timeout 271
 - while routing 261
 - with multiple hosts 261
- delivery processes 253–255
 - controlling how many 254
 - holding domains 255
 - limiting number of 252
 - order of delivery 255
 - partial delivery 255
- Delivery-date*: header line 43, 154
 - input processing 373
- delivery_date_add* option 154
- delivery_date_remove* option 155
- deliver_drop_privilege* option 459
- deliver_queue_load_max* option 62
- deny verb in ACLs 321
- /dev/null*
 - compared with `:blackhole:` 143
 - redirection to 142
- dial-up hosts *see* intermittently connected hosts
- dial-up user list *see* DUL (Dial-up User List)
- digital signature 98
- directory
 - current, in transports 115, 152
 - for building Exim 550
 - for mailboxes, limitation 67
 - home, in transports 115, 152
 - multilevel mailboxes 67
 - spool, creation of 551
 - spool, splitting 240
- directory option 191
- directory search lookup 395
- directory_mode* option 191
- directory_transport* option 224
- disable_ipv6* option 64
- disabling
 - delivery at high load 248
 - filter features 213
 - IPv6 64
- disabling (*continued*)
 - message logs 241
- discard verb in ACLs 322
- discarding address by redirection 143
- disclaimers, adding 98
- disk
 - checking free space 63
 - performance 68
- DN= in log lines 280
- DNS (Domain Name System)
 - A record 20
 - AAAA record 20
 - avoiding repeated lookups 124, 134
 - black lists 333–336
 - caching 22
 - CNAME record 25, 470
 - common errors 25
 - control parameters 124
 - dnslookup** router 123
 - domain syntax precheck 473
 - logging lookup failure 513
 - lookup parameters 473
 - master and slave servers 21
 - MX records, broken 25
 - MX records, use of 23, 123
 - name servers 21
 - NS record 26
 - overview 20–26
 - PTR record 24–25
 - qualifying incomplete names 124
 - query-style lookup 404
 - querying specific servers 26
 - records for mail routing 23
 - reverse lookup 24
 - reverse lookup for host list 450–451
 - servers out of step 26
 - syntax of domain and host names 21
 - temporary errors 261
 - temporary errors, long-term 473
 - timeouts in routers 116–117
 - widening domains 124
 - wildcard MX records 125
 - zones 21–22
- dnsdb lookup type 404
- dnslists ACL condition 334–336
- \$dnslist_domain* variable 335
- \$dnslist_text* variable 335
- \$dnslist_value* variable 335
- dnslookup** router 38, 42, 123–126

- dnslookup** router (*continued*)
 - DNS parameters 124
 - domain widening 125
 - header rewriting 126
 - MX records, processing conditionally 125
 - routing the same domain 124
 - `dns_again_means_nonexist` option 473
 - `dns_check_names_pattern` option 473
 - `dns_qualify_single` option 173
 - `dns_retrans` option 473
 - `dns_retry` option 473
 - `dns_search_parents` option 174
 - dollar *see* \$ (dollar)
 - domain
 - default for qualification 60
 - definition of 10
 - including in aliases 76
 - incomplete, rewriting 375
 - mixed local and remote 88–89
 - name, definition of 20
 - omitting in aliases 76
 - restricting in routers 104
 - routed to local host 117–119
 - virtual 74–78
 - virtual, default recipients 76–77
 - virtual, multiple lists 74
 - virtual, postmaster for 77–78
 - virtual, single list for several 76
 - domain ACL condition 339
 - domain, host, and address lists 440–455
 - domain lists (*see also* lists) 58, 444–447
 - host names in 445
 - in file 72
 - lookup items in 446–447
 - MX domain in 445
 - regular expressions in 446
 - wildcard domains in 445
 - domain literal addresses 127, 469–470
 - `$domain` variable
 - in batch delivery 175
 - in rewriting rules 380
 - in system filter 208
 - in transports 153, 166
 - when scanning lists 73
 - domains option 73
 - vs* `route_list` in **manualroute** 129
 - `$domain_data` variable 339, 447
 - dot *see* . (dot)
 - double-quote *see* " (double-quote)
 - Dovecot 295
 - driver option
 - in authenticators 289
 - in routers 100
 - in transports 151
 - drivers
 - definition of 33
 - list of all 34
 - drop verb in ACLs 322
 - dsearch lookup type 395
 - DSN (Delivery Status Notification) 2
 - DT= in log lines 513
 - DUL (Dial-up User List) 333
 - duplicate addresses 44
 - in redirection list 140
- ## E
- EHLO SMTP command 306
 - avoiding use of 168
 - data for outgoing 168
 - error response 258
 - syntax errors, accepting 308
 - underscore in host names 308
 - usage 14
 - verifying 307–308
 - empty *Bcc*: header line 12
 - empty sender 13, 204, 205, 226
 - testing for 234, 337, 452
 - when verifying 339
 - with `-f` option 485
 - encrypted ACL condition 336
 - encryption
 - of password 423
 - of SMTP connections 16, 276–281
 - requiring for AUTH 341
 - endpass ACL modifier 326
 - ends filter condition 230
 - envelope
 - definition of 11
 - SMTP format 11
 - envelope sender *see* sender address
 - Envelope-to*: header line 12, 43, 154
 - input processing 373
 - `envelope_to_add` option 154, 175
 - `envelope_to_remove` option 155
 - environment
 - for **pipe** transport command 199–200
 - for transports 151

- environment option 199
- equals sign *see* = (equals)
- errors (*see also* delivery errors)
 - in BSMTP input 299
 - in DNS data 25
 - temporary in lookups 406
 - while receiving non-SMTP messages 487
- errors_copy option 474
- errors_reply_to option 474
- errors_to option 79, 149, 478
 - in *deliver* filter command 223
- error_message filter condition 234
- escape_string option 178
 - with BSMTP 180
- escaping
 - forcing in expansion 416
 - in Exim filters 219
 - in filter test output 217
 - in log lines 202
 - in mail filter command 227
 - in pipe commands 142, 198, 224
 - in quoted strings 149
 - in string expansion 407–408
 - lines for BSMTP 180
 - local delivery lines 85, 178
- /etc/hosts* file 274
- /etc/mail/mailer.conf* file 554
- /etc/passwd* file 105, 114, 292, 423, 434
- /etc/services* file 169
- ETRN SMTP command 243, 297–298
 - using an external command 298
- exclamation mark *see* ! (exclamation mark)
- +exclude_unknown in DNS black lists 334
- exigrep* utility 523
- Exim filter 2
 - bounce message, testing for 234
 - case-sensitivity in conditions 230
 - command descriptions 221–229
 - command examples 209–212
 - command *see individual commands*
 - comments in 218
 - compared with external delivery agent 212
 - conditional example 210
 - conditions 229–235
 - delivery status, testing for 234
 - disabling features 213
 - format 218–220
 - forwarding example 209
- Exim filter (*continued*)
 - ignoring errors 225
 - list of addresses, testing 234–235
 - logging commands 228–229
 - numeric testing 232
 - personal mail, testing for 232–234
 - Sieve filter, compared with 208
 - significant actions 220–221
 - significant actions, testing for 234
 - string testing 230–232
 - system filter, example of 215–216
 - system filter, setting up 214–215
 - testing 216–218
 - user filter 208
 - user filter, setting up 212–214
 - vacation example 209
 - variables 221
 - while transporting 99
- Exim gid 456
- Exim monitor 528–535
 - Hide button 532
 - log display 531
 - main action buttons 530
 - queue display 532
 - queue menu 533–535
 - Quit button 530
 - searching 531
 - seeing messages on the spool 529
 - Size button 530
 - starting 528
 - stripcharts 530
 - Update button 532
 - window appearance 528
- Exim uid 456
- exim-process.info* file 526
- eximon* utility 50, 528
- eximstats* utility 523–525
- exim_checkaccess* utility 535
- exim_dbmbuild* utility 72, 393, 536–537
- exim_dumpdb* utility 525
- exim_lock* utility 539
- exim_tidydb* utility 244, 537–539
- exinext* utility 525
- exipick* utility 493
- exiqsumm* utility 525
- exiwhat* utility 526–528
- expansion 407–439
 - ACL conditions and modifiers 323
 - and condition 427

expansion (continued)

- authentication tests 423–426
- case forcing 413
- character translation 419
- combining conditions 427
- conditional 82, 419–428
- crypteq condition 423
- def condition 426
- delivery state, testing 427
- domain operator 432
- encrypted string equality test 423–424
- eq condition 420
- escape operator 416
- escaping literals 407–408
- escaping substrings 407–408
- eval and eval10 operators 416
- exists condition 106, 213, 427, 430
- expand operator 417
- extract item 432–435
- extracting named fields 432–434
- extracting unnamed fields 434–435
- file existence, testing 427
- file insertion 432
- first_delivery condition 427
- forcing failure 57, 428
- hash operators 412
- header insertion 409–410
- header line, testing existence 426
- if item 82
- in Exim filters 219
- incorrect syntax 57
- introduction 39
- IP address masking 413
- lc operator 413
- LDAP authentication 425
- ldapauth condition 425
- length operator 410–411
- local_part operator 432
- locking out features in Exim filters 438
- lookup item 429
- lookups 429–432
- mask operator 413
- match condition 421
- matching lists 422
- match_address condition 422
- match_domain condition 422
- match_ip condition 422
- match_local_part condition 422
- multiple times 417

expansion (continued)

- negated condition 421
- nhash operator 412
- numeric comparisons 426
- of mailing lists 81
- of **pipe** transport command 198–199
- of quota option 193
- or condition 427
- PAM authentication 424–425
- pam condition 424
- partial lookups 430
- perl item 214, 437
- prvs item 353
- prvscheck item 354–355
- query-style lookups 431
- quote operator 413
- quote_local_part operator 414
- quote_xxx operators 415
- quoting 413–416
- quoting for lookup 415
- quoting local parts 414
- quoting printing data 416
- quoting regular expression data 414
- Radius authentication 425
- radius condition 425
- readfile item 214, 401
- readsocket item 214, 435
- regular expression condition 421
- rewriting rule replacement 380
- run item 214, 436
- running an external program 436–437
- running embedded Perl 437–438
- rxquote operator 414
- saslauthd authentication 425
- saslauthd condition 425
- sg item 419
- simple arithmetic 416
- single-key lookups 429–431
- socket communication 435–436
- special characters 407
- splitting addresses 432
- string equality test 420
- substr operator 411–412
- substring extraction 410–412
- summary 556–582
- testing 438
- text substitution 419
- tr item 419
- translating characters 419

- expansion (*continued*)
 - uc operator 413
 - variable, substitution 409
 - variable, testing empty 426
 - EXPN SMTP command 296–297
 - skipping routers when processing 104
 - external command for routing 134
 - external delivery agent 85–86
 - compared with filter 212
 - external host, virus checking on 97–98
 - extract_addresses_remove_
 - arguments option 303, 483
- F**
- F= in log lines 515
 - F option 370, 485
 - f option 84, 94, 217, 304, 464, 484–485
 - removing restriction on use 465
 - :fail:
 - in redirection lists 82, 143
 - interaction with ACL 327, 328
 - fail (router outcome)
 - definition of 37
 - forcing 143–144
 - fail filter command 236
 - fail in expanded strings 428, 429, 436
 - fallback hosts 173
 - set in routers 115–116
 - fallback_hosts option
 - in routers 115
 - in **smtp** transport 173
 - fcntl() locking function 68, 188
 - FIFO (named pipe) delivering to 183
 - file lookup *see* lookup
 - file option
 - in **appendfile** transport 181, 191
 - in **autoreply** transport 206
 - in **redirect** router 79, 137
 - files
 - attribute check in **redirect** 145
 - cdb format 75
 - existence testing in expansions 427
 - for each message 239–241
 - group, disabling check 145
 - hints 30, 242–244
 - indexed 72
 - locking with lock file 187–188
 - locking with lock function 188
 - files (*continued*)
 - mailbox locking in **appendfile** 187–190
 - maintaining aliases 536–537
 - message logs 241
 - mode check in **appendfile** 184
 - non-existent, creating 183
 - one per message 190–192
 - owner check in **appendfile** 184
 - owner, disabling check 145
 - restricting router by existence 105–106
 - shared by Exim processes 238–244
 - system aliases 39
 - file_expand option 206
 - file_format option 186
 - file_must_exist option 183, 460
 - file_optional option 206
 - file_transport option 48, 146, 213
 - filter
 - Exim *see* Exim filter
 - Exim vs Sieve 208
 - Sieve *see* Sieve filter
 - system *see* system filter
 - with multiple user addresses 87
 - filtering messages 208–237
 - in transports 160–163
 - filter_prepend_home option 224
 - final_timeout option 170
 - finish filter command 211, 229
 - first_delivery filter condition 234
 - flock() locking function 188
 - foranyaddress filter condition 234
 - forbid_blackhole option 143
 - forbid_exim_filter option 213
 - forbid_file option 79, 148, 213
 - forbid_filter_xxx options 213–214
 - forbid_include option 143
 - forbid_pipe option 79, 148, 214
 - forbid_sieve_filter option 213
 - forced expansion failure 57
 - forgery of mail 16
 - format
 - of address 10
 - of mailboxes 185–186, 191
 - of messages 9
 - .forward files
 - broken, telling the user 149–150
 - bypassing 101, 149
 - skipping when verifying 103, 139
 - when filtering 208

forward slash *see* / (forward slash)
 forwarding
 filter example 209
 interaction with aliasing 141
 FreeBSD
 indexed password file 66
 killall command 527
 MTA configuration 554
 ports mechanism 541
 freeze control 330
freeze filter command 236–237
freeze_exec_fail option 202
From: header line 11, 226, 485
 “From” line (for sender address) 304, 369
 as message separator 177
 when filter testing 216, 217
from option 205
 frozen messages 45, 60–61, 254
 forcing in queue runs 488
 ignoring or discarding bounces 61

G

gcc (GNU C compiler) 541
gdbm (GNU DBM) 393
 “gecos” field 370, 485
gecos_name option 370
gecos_pattern option 370
 generated addresses *see* child addresses
 generic options
 for routers 100–121
 for transports 151–164
gethostbyname option
 smtp transport 173
 GMT (Greenwich Mean Time)
 in timestamps 472
 offset from 581
 GNU/Linux
 binary distributions 541
 DBM library for 541
 file system performance 67
 killall command 527
 syslog performance 506
 TZ variable 472
 GnuTLS 276
 GPL (GNU General Public License) 1
 group
 for mailbox directory access 182

group (*continued*)
 set in routers 113–115
 special for local delivery 152
 supplementary list 152
group option
 in routers 48
 in transports 48, 152

H

-H file 239, 250
 H= in log lines 517
 hardware for busy sites 68
 hash *see also* # (hash, sharp sign)
 expansion operators 412
 for certificate directory 279
 numeric 67
 header lines
 added by ACL 322
 adding in filters 237
 adding in routers 111–113
 adding in transports 154–156
 checking in ACLs 340–341
 definition of 10
 extracting recipients from 303, 483
 forged 16
 in expanded strings 409–410
 removing in filters 237
 removing in routers 111–113
 removing in transports 154–156
 rewriting at reception time 376
 rewriting in **dnslookup** router 126
 rewriting in transports 157, 377
 syntax of 10
 testing for existence 426
 verifying syntax of 340
headers add filter command 237
headers option 206
headers remove filter command 237
headers_add option
 in routers 111
 in transports 155
 not allowed with *one_time* 148
headers_only option 154
headers_remove option
 in routers 111
 in transports 155
 not allowed with *one_time* 148
headers_rewrite option 157, 377

- HELO SMTP command (*see also* EHLO)
 - including in BSMTP 179
- helo_accept_junk_hosts 308
- helo_allow_chars option 308
- helo_data option 168
- helo_lookup_domains option 307
- helo_try_verify_hosts option 307, 337
- helo_verify_hosts option 307
- Hide button (Exim monitor) 532
- hide in option settings 56, 401
- hide_child_in_errmsg option 139
- hiding
 - child address in error message 139
 - configuration data 56, 401
- high load, reducing Exim's activity at 61–62
- hints 30, 242–244
 - database maintenance 537–539
 - deleting on reboot 167
 - for reusing connections 167
 - for serialized host connections 167
 - tidying 244
 - updating 46
- hold_domains option 255
- home directory
 - in transports 152
 - mailbox in 181
 - set in router for transport 115
- \$home* variable 105, 152
 - in routers 100
 - in user filter 224
- home_directory option 152
- host(s)
 - alias names for 451
 - authenticating 170, 281–295
 - blocking 332
 - checking in ACLs 332–333
 - fallback 115–116
 - looking up name from IP address 306–307
 - multihomed 168, 174
 - overriding in transports 172
 - randomizing in **manualroute** router 130
 - randomizing in **smtp** transport 173
 - serializing connections to 167
 - specifying in **smtp** transport 172–174
 - underscore in names 308
 - verifying names 306–307
- host errors 258–259
- host lists (*see also* lists) 58, 447–452
 - host lists (*continued*)
 - DNS forward lookup 450
 - DNS reverse lookup 450–451
 - empty items in 447
 - host lookup failure 450
 - host name, use of 450–451
 - IP address checking 448–450
 - IP address lookup item 449–450
 - IP address, masked 448–450
 - IPv6 addresses 449
 - local host, testing for 447
 - local interfaces 448
 - name lookup item 452
 - names vs IP addresses 452
 - order of items 451
 - query-style lookup 450
 - regular expressions 452
 - single-key lookup 449
 - unknown host name, accepting 451
 - wildcard names 451
 - host names
 - as email domains 23
 - finding from IP addresses 24
 - in local transports 133
 - in retry rules 263
 - syntax of 21
 - underscore in 308
 - UUCP 90
 - verifying 306–307
 - \$host* variable 90, 133, 161, 281, 288
 - hostmaster 25
 - hosts ACL condition 332–333
 - hosts option 89, 172
 - hosts_avoid_esmtp option 168
 - hosts_avoid_tls option 280
 - hosts_max_try option 166
 - hosts_max_try_hardlimit option 167
 - hosts_override option 172
 - hosts_randomize option
 - in **manualroute** router 130
 - in **smtp** transport 97, 173
 - hosts_require_auth option 170, 264, 288
 - hosts_require_tls option 280
 - hosts_try_auth option 170, 288
 - \$host_address* variable 161, 281, 288
 - host_find_failed option 129–130
 - host_lookup option 306
 - hub, mail *see* mail hub

hyphen *see* - (hyphen)

I

I= in log lines 513
 -i option 482
 ibase lookup type 402–403
 ibase_servers option 403
 ident protocol *see* RFC 1413
 identifying messages 49
 if expansion item 82
 if filter command 229
 .ifdef in configuration files 56
 IFS setting
 in command for **pipe** transport 86
 in *pipe* filter command 225
 not needed in pipe command 198
 ignore_bounce_errors_after option 61, 338
 ignore_fromline_hosts option 370
 ignore_status option 47, 201
 ignore_target_hosts option 109
 IMAP (Interactive Mail Access Protocol) 6
 Cyrus server 203
 mailbox format 191
 use of password file 66
 in-addr.arpa domain 24
 In-Reply-To: header line 226
 :include:
 in mailing lists 80
 in redirection lists 143
 .include in configuration files 54, 536
 +include_unknown
 in DNS black lists 334
 in host lists 451
 incoming SMTP connections
 controlling 62–63
 indexed file 72
 indexed password file 66
 inetd 30, 482
 configuration 295
 initgroups option 115, 152
 input directory, splitting 240
 installing Exim 551–552
 alternative approaches 541
 info documentation 554
 naming the binary 551
 InterBase 402–403

interface
 choosing outgoing 168
 logging incoming 513
 setting up for listening 246
 interface option 168
 intermittently connected hosts 271–275
 holding incoming mail for 68, 132,
 272–273
 incoming messages, accepting 275
 use of daemon 274
 use of Exim on 273–275
 use of queue_only_file option 251
 Internet mail, general description 4–27
 Internet message standards 9
 I/O errors 258
 IP addresses
 checking in host lists 448–450
 ignoring erroneous in routers 109
 in **ipliteral** router 127
 in MX records 471
 looking up in **manualroute** router 129
 looking up in **smtplib** transport 173
 masking 413
 ip6.arpa domain 24
ipliteral router 127, 470
 ipsearch lookup type 392
 IPv4 address format 20
 IPv6
 address format 20
 address format in host lookups 449
 disabling 64
 forcing use of 64
 in host lists 449
 interface option 169
 is filter condition 231

J

-J files 241
 journal files 241
 junk mail 16, 20, 60, 300

K

Kerberos 295
 kill command 51, 536
 killall command 527
 killing processes, commands for 527
 killing the daemon 246

L

- large installations 66–70
 - hardware configuration 68–70
- large message queues 65
- LDAP 399–402
 - authentication 400–401, 425
 - data returned 401–402
 - DN lookup 401
 - encrypted data 423
 - multiple entry lookup 401
 - quoting rule 415
- ldap lookup type 399–402
- ldapdn lookup type 401
- ldapm lookup type 401
- ldap_default_servers option 399
- left angle bracket *see* < (left angle bracket)
- LF (linefeed) 9, 301, 471, 484
 - in local delivery 179
- limiting
 - client bandwidth 343
 - connection rate 343
 - incoming connections 62–63
 - message arrival rate 308–309, 342–344
 - message size 63
 - message size in transports 154
 - number of delivery processes 65
 - output from pipe 202
 - parallel remote delivery 64, 254
 - SMTP command rate 343
- line termination 9
- linear password file 66
- linefeed *see* LF (linefeed)
- Linux *see* GNU/Linux
- List-: header lines 476
- lists 440–455
 - address lists 452–455
 - changing separator character 440
 - comments in interpolated files 442
 - common structure 440–443
 - domain lists 444–447
 - file interpolation 442
 - host lists 447–452
 - local part lists 455
 - lookup items 442
 - named 443
 - named, compared with macros 59
 - named, maximum number of 443
 - named, overview 59–60
 - negative items in 440–441
 - lists (*continued*)
 - separator character 59, 440
 - whitespace in 58
- LMTTP (Local Mail Transfer Protocol) 203, 298
 - in **smtp** transport 171
- lmtpp** transport 203–204
 - affixes in RCPT 157
 - batching addresses in 174–176
 - use of `batch_max` option 204
- `lmtpp_ignore_quota` option 171
- load on system
 - queueing messages when high 251
 - reducing Exim's activity when high 61–62
- local delivery
 - batched SMTP 179–180
 - errors 261
 - escaping lines 178
 - line terminators 179
 - message separators 176–178
 - setting environment in routers 113–115
 - use of retry rules 263–264
 - user and group set in routers 113–115
 - with special group 152
- Local directory 543
- local domains
 - multiple 71–74
 - multiple, differentiating between 73
- local host
 - in **smtp** transport `hosts` option 174
 - routing to 117–119
 - virus checking on 94–96
- local message (non-SMTP) 482–484
 - line termination 484
- local part
 - case-sensitive 92–93
 - definition of 10
 - ignoring for local delivery 90–92
 - prefix/suffix 81, 87, 101–102, 372
 - prefix/suffix, in RCPT 157
 - restricting in routers 104
 - unqualified in redirection data 141
 - unusual characters in 313
 - use in retrying 120, 164
- local part lists (*see also* lists) 455
- local routing data 88
- local scan function 367
- local SMTP 298–299
- local transport, batching addresses 174–176

- local user, checking in routers 105
- localhost_number option 49
- locally submitted message
 - envelope sender for 84
 - specifying in ACL 330
 - testing for 447
- Local/Makefile* 543–548
- local_from_check option 372, 464, 485
- local_from_prefix option 372
- local_interfaces option 246
- \$local_part* variable
 - in batch delivery 175
 - in rewriting rules 380
 - in system filter 208
 - in transports 153
- local_parts ACL condition 339
- local_parts option 78, 89
- \$local_part_data* variable 89, 339, 447
- local_part_prefix option 81
- \$local_part_prefix* variable 101
- local_part_prefix_optional option 102
- local_part_suffix option 81
- \$local_part_suffix* variable 101
- local_part_suffix_optional option 102
- local_scan()* function 367
- local_sender_retain option 372
- location of mailboxes 181–183
- lock files 187–188
 - creating 189
 - not using 68, 189
 - reason for using 188
- lockf()* locking function 188
- lockfile_mode option 189
- lockfile_timeout option 189
- locking *see also* mailbox locking
 - fcntl()* function 68
 - flock()* function 188
 - lockf()* function 188
 - message files 242
- lock_fcntl_timeout option 189, 190
- lock_interval option 189
- lock_retries option 189
- log files 244, 505–506
 - cycling 507–508
 - datestamped 508
 - extracting information from 523–525
 - overview 50
- log files (*continued*)
 - per-message 241
 - reject and message logs, suppressing 506
 - searching 523
- log line tags *see* individual tags
- summary 522
- log option 207
- log selectors summary 511
- logfile* filter command 228
- logging
 - autoreply messages 228
 - deferred delivery 521
 - deliveries 519–521
 - delivery failure 521
 - destination, control of 506–509
 - increasing or reducing 510–516
 - main log entries 517–522
 - message reception 517–519
 - multiple SMTP recipients 520
 - style of 109
 - summary of fields 522
 - summary of selectors 511
 - suppressed delivery 502
 - timestamps 471, 517
 - to *syslog* 506, 509–510
- logwrite ACL modifier 326
- logwrite* filter command 228
- log_as_local option 110
- log_defer_output option 202
- log_fail_output option 202
- log_file_path option 506
- log_message ACL modifier 327
- log_output option 202
- lookup expansion, disabling in filters 213
- lookups 389–406
 - by name in host lists 452
 - caching 406
 - cdb 394–395
 - dbm 393–394
 - dbmnz 394
 - dnsdb 404
 - dsearch 395
 - in domain lists 446–447
 - in expanded strings 429–432
 - in lists 442
 - including at build time 545
 - InterBase 402–403
 - IP address in host list 449–450
 - iplsearch 392

lookups (*continued*)
 ldap 399–402
 LDAP, data returned 401–402
 LDAP, DN lookup 401
 LDAP, lookup types 401
 LDAP, multiple entry lookup 401
 ldapdn 401
 ldapm 401
 lsearch 391
 MySQL 402–403
 nis 395
 nisplus 405
 nwildlsearch 391
 Oracle 402–403
 overview 57–58
 passwd 405
 PostgreSQL 402–403
 query-style 398–406
 query-style, overview 390
 quoting data in queries 398
 single-key 390–398
 single-key, default values 396
 single-key, overview 390
 single-key, partial matching 396–398
 SQL 402–403
 SQLite 402–403
 styles 389–390
 temporary errors 406
 usage 389–390
 whoson 406
 wildlsearch 391
 lookup_open_max option 406
 loopback address 250, 301
 loopback interface 62, 274, 300, 315
 loops while routing 45
 lsearch lookup type 391

M

-M option 62, 254, 465
 -M.. options 352, 493–494
 macros
 changing the values of 55
 compared with named lists 59
 example 55
 in configuration files 54–55
 overriding on command line 492
 mail filter command 225–228
 disabling 214

mail hub
 definition 133
 using a **manualroute** router 133
 mail routing *see* routing
 MAIL SMTP command 14
 error response to 259
 for BSMTP 299
 rate limiting 308
 timeout after 259
 mailbox directory
 multiple levels 67
 performance limitation 67
 mailbox format 185–186
 Berkeley 176
 changing transport for 186
 maildir 68, 191–192
 MBX 185
 MMDf 177, 178
 mailbox locking 187–190
 avoiding 68
 failure of 67
 fcntl(), blocking and non-blocking 189
 lock files 187–188
 lock files, why use? 188
 MBX rules 190
 options in **appendfile** 189–190
 performance 189
 single-file vs multi-file 180
 with lock function 188
 with NFS 188
 mailboxes
 FIFO 183
 group access to directory 182
 in home directory 181
 in multiple directories 410, 412
 in shared directory 182–183
 location of 181–183
 lock avoidance 68
 maildir format 68, 191–192
 maintenance 539–540
 mode checking in **appendfile** 184
 mode for unprivileged delivery 460
 NFS-mounted 68
 owner checking in **appendfile** 184
 quota control 192–196
 quota for number of files 193
 quota, inclusive and exclusive 195
 quota, warning message 195
 simultaneous delivery into 67

- mailboxes (*continued*)
 - symbolic links 183
- maildir++ 194
- maildir format mailboxes 68, 191–192
 - maildir tags 194
 - maildirsize files 194
 - quota control 193
- maildir_format option 192
- maildir_quota_directory_regex option 194
- maildir_tag option 192, 194
- maildir_use_size_file option 194
- mailing lists 78–85
 - automatic subscription 83
 - closed 81–83
 - independent managers 78
 - NFS-mounted 80
 - re-expansion, suppressing 81
 - scanning postings 83
 - syntax errors in 80
 - using external software 83–85
- mailq command 50, 503
- main log 50, 505
 - format of entries 517–522
- Majordomo 83
- manual routing 88
- manually_thawed condition 493
- manualroute** router 88, 127–134
 - bydns in route_list 129
 - inline routing rules 127–131
 - looked-up routing rules 131–132
 - looking up IP addresses 129
 - non-existent hosts 129–130
 - port, with host 130
 - randomizing host order 130
 - repeat routing 134
 - routing to a local transport 132
 - transport settings for 134
 - use for mail hub 133
- masking IP addresses
 - in expansions 413, 450
 - in host lists 448–450
- matches filter condition 231
- maximum *see* limiting
- max_output option 202
- max_rcpt option 153, 159, 166
- MBX format mailboxes 185
 - locking rules 190
- mbx_format option 185
- MD5, for password encryption 423
- message
 - 8-bit bytes 301
 - additions by MUA and MTA 11
 - attachments 10
 - blocking 19
 - body, definition of 10
 - body not modified 301
 - cancelling 493
 - checking for virus or spam 162
 - checking incoming 17–20
 - copying 108
 - encoding body 3
 - envelope sender for local submission 84
 - file format 239–241
 - filtering 208–237
 - forcing delivery 493
 - format of 9–11
 - freezing and thawing 493
 - from local process 302–305
 - header, definition of 10
 - identifying 49
 - incoming processing 368–374
 - inspecting contents 493
 - limiting arrival rate of 308–309, 342–344
 - limiting size of 63
 - modifying body 98–99
 - modifying envelope 494
 - non-SMTP, timeout 483
 - “on the wire” 11–13
 - queueing incoming 250–251, 330, 487
 - recipients when locally submitted 302–303
 - scanning for viruses 93–98
 - sender when locally submitted 304–305
 - separator for local delivery 176–178
 - signed 98
 - size control, global 301
 - size control in transports 154
 - sources of 300–306
 - submission 330
 - submission, problems with remote MUA 6
 - transporting header or body only 154
- message ACL modifier 327
- message errors 259
- message files
 - format of 239–241
 - locking 242
- message ID 66
 - description of 49

- message ID (*continued*)
 - in acceptance responses 296
 - uniqueness of 49–50
- “Message is frozen” 254
- message log files 241, 506
 - suppressing 69, 506
- message queue *see* queue
- message routing *see* routing
- message store
 - Cyrus 203
 - description 203
- Message-ID*: header line 12
 - input processing 373
- \$message_age* variable 70
- message_id_header_text* option 373
- message_logs* option 69, 241, 506
- message_prefix* option 177–178
 - for MBX mailbox 185
 - with BSMTP 179
 - with *directory* option 191
- \$message_size* variable 107, 192
 - in ACLs 320
- message_size_limit* option 296, 301
 - for all messages 63
 - for individual transports 154
- message_suffix* option 177–178
 - for MBX mailbox 185
 - with BSMTP 179
 - with *directory* option 191
- MH user agent 315
- MIME parts
 - decoding 365
 - scanning 362–365
 - scanning with regular expressions 366
- MIME-Version*: header line 12
- mimencode* command 288
- \$mime_xxx* variables 362–365
- minimal configuration file 52
- misc* database 243
- mixed local/remote domains 88–89
- MMDF mailbox format 177, 178
- mode
 - checking in **appendfile** transport 184
 - checking in **redirect** router 145
 - in *logfile* filter command 228
 - in *save* filter command 223
 - mailboxes for unprivileged delivery 460
 - of **autoreply** log file 207
 - of created directory 191
 - mode* (*continued*)
 - of lock files 189
 - of log files 466
 - of message files 457
 - of spool files 466, 546
 - mode option
 - in **appendfile** transport 184, 460
 - in **autoreply** transport 207
 - modemask option 145
 - mode_fail_narrower* option 184
 - monitoring Exim 525–535
 - more option 36, 116
 - overriding 130
 - with *route_list* in **manualroute** 129
 - Mset option 439
 - MTA (Mail Transfer Agent)
 - backup 8
 - intermediate 7
 - job description 4
 - types of 8
 - MUA (Mail User Agent)
 - job description 4
 - on workstation 6
 - use of SMTP 6
 - mua_wrapper* option 461
 - multilevel mailbox directories 67
 - multiple local domains 71–74
 - multiple user addresses 86–88
 - multi_domain* option 166
 - MX (DNS mail exchange record) 23
 - backup, detecting in ACLs 339
 - broken 25, 471
 - non-existent 126
 - processing conditionally 125
 - recognizing secondary 125
 - required to exist 126
 - using for routing 123
 - when not present 23
 - @mx_any 340, 445
 - mx_domains* option 126
 - @mx_primary 340, 445
 - @mx_secondary 340, 445
 - MySQL 402–403
 - mysql* lookup type 402–403
 - mysql_servers* option 403
- N**
 - N option 500, 521

- \$n0–\$n9* variables 221
 - name servers
 - description 21
 - minimizing delays in 68
 - named lists 443
 - compared with macros 59
 - maximum number of 443
 - overview 59–60
 - named pipe *see* FIFO (named pipe)
 - ndbm 393
 - negation in lists 39
 - interaction with macros 59
 - interaction with named lists 59
 - never_mail option 207
 - never_users option 459
 - newaliases* command 503
 - newlines
 - in data from a *dnsdb* lookup 404
 - in data from an LDAP lookup 401
 - in data from an SQL lookup 403
 - in *echo* command 288
 - in Exim filters 219
 - in file insertions 432
 - in header insertions 409
 - in *logwrite* filter commands 228
 - in *lsearch* files 39, 391
 - in mailbox files 177
 - in message ACL modifiers 328
 - in redirection lists 139, 140, 143
 - when adding header lines 112, 155, 237
 - NFS (Network File System)
 - lock files used with 188
 - mailboxes mounted on 68
 - mailing lists mounted on 80
 - nhash example 67
 - NIS 66, 395
 - nis lookup type 395
 - nisplus lookup type 405
 - NMH user agent 315
 - noerror in filter command 225
 - non-ASCII characters 467–468
 - non-existent file, creating 183
 - NS (DNS name server record) 26
 - NTLM *see* SPA
 - nwildlsearch lookup type 391
- O**
- oA option 503
 - od... options 486–487
 - oe... options 487–488
 - oi option 303, 482
 - oM... options 485–486
 - filter testing 218
 - oMr option 94
 - once option 207
 - once-only autoreply 227
 - once_repeat option 207, 227
 - one-time redirection 148
 - one_time option 148
 - in **redirect** router 81
 - open relays
 - definition of 19
 - in DNS black lists 333
 - testing programs 314
 - OpenSSL 276
 - operations overview 49–70
 - options
 - Boolean values 53
 - build-time 32
 - common for **appendfile** and **pipe** transports 176–180
 - common to all authenticators 289–290
 - generic for routers 100–121
 - generic for transports 151–164
 - hiding data in 56, 401
 - mailbox locking in **appendfile** 189–190
 - quote usage in 53
 - runtime 32
 - syntax of 53
 - time interval values 53
 - or option 483
 - Oracle 402–403
 - oracle lookup type 402–403
 - oracle_servers option 403
 - OS directory 544
 - os option 482
 - output from pipe 202
 - owners option 145
 - owngroups option 145
 - oX option 247, 481
- P**
- P= in log lines 515, 518
 - PAM (Pluggable Authentication Modules) 424–425
 - panic log 50, 506

- parallel processing 30
 - in remote delivery 254
 - in remote delivery, limiting 64
 - in routing 83
- parentheses *see* () (parentheses)
- partial matching in single-key lookup 396–398
- pass (router outcome) 116
 - definition 37
- passwd lookup type 405
- password file
 - indexed 66
 - information from 485
 - linear 66
 - used by IMAP and POP 66
- passwords, encrypted 423
- pass_on_timeout option 117
- pass_router option 117
- path option 197
- pathname, redirecting to 142
 - pd option 437
- “percent hack” 384
- percent *see* % (percent)
- performance
 - disabling reject and message logs 506
 - disk I/O 68
 - hardware considerations 68
 - holding mail for dial-up hosts 272
 - improving with *fcntl()* locking 68, 189
 - many messages for one host 489
 - many messages in one file 191
 - of file system 67
 - of lookups 393
 - of *syslog* 506
 - parallel remote delivery 64
 - reducing database queries 431
 - repeatedly routing same domain 124, 134
 - with large message queue 65, 240
- Perl
 - calling from expanded string 437–438
 - DBM functions 394
 - embedded 214
- perl expansion item, disabling in filters 214
- perl_at_start option 437
- perl_startup option 437
- “Permission Denied” for
 - require_files 106
- personal filter condition 232
- pgsql lookup type 402–403
- pgsql_servers option 403
- Pine user agent 185
- pipe
 - error return from 261
 - redirecting to 142
- pipe filter command 224–225
 - disabling 214
- pipe symbol *see* | (vertical bar)
- pipe** transport 47, 196–203
 - affixes in RCPT for BSMTP 157
 - batching addresses in 174–176
 - compared with **autoreply** 204
 - defining the command 196–197
 - environment for command 199–200
 - error handling 201
 - expansion of command 198–199
 - IFS not needed 198
 - options in common with **appendfile** 176–180
 - output handling 202
 - parsing the command 198–199
 - restrictions on command 201
 - shell, not used by default 198
 - shell, using 199
 - temporary errors 201
 - timeout for command 200
 - user and group 197
- pipelining 13
- \$pipe_addresses* variable
 - in **pipe** transport 199
 - in transport filter 161
- pipe_transport option 47, 146, 213
- pkill* command 527
- plaintext** authenticator
 - in a client 293
 - in a server 290–293
 - password checking 292–293
- plus *see* + (plus)
- policy controls 306–345
 - for blocking messages 19
 - testing 497–499
- POP (Post Office Protocol) 6
 - mailbox format 191
 - use of password file 66
- port option 169, 171
- ports
 - for incoming connections, logging 513
 - for outgoing connections 169
 - for outgoing connections, logging 514
 - in **manualroute** router 130

- ports (*continued*)
 - used by daemon 247
 - PostgreSQL 402–403
 - postmaster
 - accepting address in ACLs 314
 - for virtual domains 77–78
 - role of 27
 - unqualified address 305
 - Precedence*: header line 476
 - preconditions for routers 35, 101–107
 - prefix for local part 81, 87
 - in RCPT 157
 - preserve_message_logs option
 - 241, 506
 - primary_hostname option 168, 445
 - print_topbitchars option 371, 517
 - private key, creating 277
 - privileged users 464–466
 - processes
 - central, lack of 245
 - commands for killing 527
 - coordination of 30
 - daemon 246–250
 - defunct 249
 - delivery 253–255
 - descriptions of types 244–256
 - design overview 30
 - limiting number of delivery 65
 - message handling, summary 255
 - overview of different types 238
 - querying 526–528
 - queue runner 30, 65, 251–253
 - reception 250–251
 - relationships 245–246
 - user and group ids 244
 - “zombie” 249
 - procmail 85–86, 197, 212
 - use of IFS 86
 - prod_requires_admin option 465
 - protocol for message submission 7
 - protocol option 169, 171
 - prvs (private signature) for BATV 352
 - checking signatures 354
 - delivering to signed addresses 355
 - signing addresses 353
 - ps command 526
 - ps option 437
 - PTR (DNS pointer record) 24–25
 - public_name option 289
 - pwcheck daemon 425
- ## Q
- q option 65, 246, 252, 465
 - q.. options 252, 488–490
 - qf option 62, 274
 - QT= in log lines 514
 - qualification domain, default 60
 - qualify_domain option 60, 84, 141, 223, 302, 305, 372
 - qualify_preserve_domain option
 - 76, 141
 - qualify_recipient option 60, 76, 141, 223, 302, 305
 - query-style lookup, definition 58
 - queryprogram** router 134–137
 - \$address_data* variable 136
 - result of command 135–137
 - question mark *see* ? (question mark)
 - queue
 - definition 29
 - implementation of 250
 - information about 492
 - inspecting 50
 - large 65
 - listing by non-admin user 465
 - number of messages on 492
 - obtaining a summary of 525
 - queue runners 251–253
 - for initial delivery only 252, 488
 - for local delivery only 252, 488
 - for specific addresses 490
 - for specific messages 490
 - including frozen messages 488
 - maximum number of simultaneous
 - 249, 252
 - options summary 491
 - order of message processing 253
 - overriding freezing 252
 - overriding retry times 252, 488
 - periodic 489
 - processing in order of message arrival 253
 - special types 252–253
 - starting 488–490
 - starting by non-admin user 465
 - two-pass processing 489
 - queueing
 - avoiding in client 461

- queueing (*continued*)
 - incoming messages 330, 487
 - queue_domains option 255, 273
 - queue_list_requires_admin option 465
 - queue_only control 330
 - queue_only option 65, 250, 252, 487
 - queue_only_file option 251
 - queue_only_load option 61, 251
 - queue_run_in_order option 253
 - queue_run_max option 65, 249, 252
 - queue_smtp_domains option 255, 274, 487
 - Quit button (Exim monitor) 530
 - QUIT SMTP command 15
 - quota
 - failure 261
 - for mailbox 192–196
 - inclusive and exclusive 195
 - retry rule for exceeding 264
 - warning message 195
 - warning threshold 195
 - quota option 193
 - quota_filecount option 193
 - quota_is_inclusive 195
 - quota_size_regexp option 194
 - quota_warn_threshold option 195
 - quote *see* " (double-quote) or ' (single-quote)
 - quoting data in lookups 398
 - quoting in expanded strings 413–416
- R**
- R= in log lines 519
 - R option 297, 490
 - Radius authentication 425
 - randomizing host lists
 - manualroute** router 130
 - smtp** transport 173
 - rate of message arrival, limiting 308–309, 342–344
 - ratelimit ACL condition 342–344
 - ratelimit database 243
 - RBL (Realtime Blackhole List) 333, 335
 - RCPT SMTP command 14, 17, 166
 - error response to 259
 - rate limiting 308
 - timeout after 259
 - use of affixes 157
 - \$rcpt_count* variable in ACLs 320
 - rcpt_include_affixes option 157
 - readfile expansion, disabling in filters 214
 - readsocket expansion, disabling in filters 214
 - reboot, deleting hints 167
 - Received:* header line 12, 16
 - input processing 373–374
 - timestamp 471
 - received_header_text option 373
 - \$received_port* variable 247
 - \$received_protocol* variable 94, 287
 - receive_timeout option 483
 - reception processes 250–251
 - reception, suspending at high system load 62
 - recipient errors 259–260
 - recipients
 - as command arguments 302
 - checking in ACLs 339
 - extracted from header lines 303, 483
 - for batched SMTP 303
 - for local SMTP 303
 - for locally submitted messages 302–303
 - recipients ACL condition 339
 - \$recipients* variable 96, 235
 - in system filter 208
 - \$recipients_count* variable
 - in ACLs 320
 - recipient_unqualified_hosts option 305
 - redirect** router 39, 40, 137–150
 - address duplication 140
 - ancestor checking 145
 - check_local_user option, use of 145
 - delivery to file 48
 - delivery to pipe 47
 - disabling certain features 145, 213
 - disabling owner and group checks 145
 - enabling certain features 145
 - file attribute checks 145
 - filter, setting up 212–214
 - redirection data, interpreting 139
 - redirection data, obtaining 137–138
 - redirection list, non-address items 142–144
 - repeated use of 145
 - rewriting child addresses 148
 - Sieve options 147
 - syntax of redirection list 140
 - transport option, must not set 137

- redirect** router (*continued*)
 - transport options 47
 - transports for files and pipes 146
- redirected addresses, processing 107
- redirecting addresses 137–150
- redirection
 - bypassing lookup default 144
 - discarding addresses 143
 - :fail: 82
 - file inclusion 80
 - forcing defer or failure 143–144
 - including a sublist 143
 - many recipients 83
 - one-time 148
 - syntax errors in data 148–149
 - to pathname or pipe 142
 - to same address 140
 - verification, effect on 351
- redirection data
 - backslash in 141
 - interpreting 139
 - non-address items in 142–144
 - obtaining 137–138
 - syntax of 140
 - unqualified local part in 141
- redirect_router option 78, 93, 107
- References*: header line 204
- \$regex_match_string* variable 366
- regular expressions
 - “ends with” example 385
 - for content scanning 366
 - in domain lists 446
 - in expanded strings 419, 421
 - matches in filters 231–232
 - quoting data in expansion 414
- reject log 50, 505
 - suppressing 506
- relaying messages
 - access checking 535
 - overview 309–311
- relay_from_hosts host list 315
- relay_to_domains domain list 316
- remote_max_parallel option 64, 65, 246, 254
- remote_sort_domains 255
- repeat_use option 145
- replies, automatic 204–207
- Reply-To*: header line 11, 226
 - in bounce messages 474
- \$reply_address* variable 226
- reply_to option 205
- reply_transport option 213
- require verb in ACLs 322
- require_files option 85, 105–106
- Resent-:* header lines 369
- restrict_to_path option 201
- retry database 242, 257
- retry rules 262–268
 - error names 264
 - examples 268
 - for quota errors 264
 - overview 262
 - parameter sets 266
 - pattern format 263
 - testing 499
 - use for local delivery 263–264
 - use for remote delivery 263
- “Retry time not reached” 521
- retry times, overriding in queue runs 488
- retrying 257–275
 - computing retry times 266–267
 - finding when next 525
 - long-term failures 269–270
 - overview 257–258
 - smtp** transport options 174
 - timeout of data 269
 - ultimate address timeout 271
 - use of local part 120, 164
 - using retry times 267
- retry_data_expire option 269
- retry_defer log selector 521
- retry_include_ip_address option 174
- retry_interval_max option 267
- retry_use_local_part option 164, 263
- return path (*see also* envelope sender)
 - changing in routers 113
 - definition of 13
 - rewriting in transports 158
- Return-path*: header line 13, 43, 155
 - filter testing 217
 - input processing 373
- return_fail_output option 90, 202
- return_message option 206, 227
- return_output option 47, 202
- return_path option 158, 159, 377
- \$return_path* variable 158
- return_path_add option 155
- return_path_remove option 155

- return_size_limit option 154, 206, 227, 301
- \$return_size_limit* variable 477
- reverse DNS lookup 24
- rewrite option 148
- rewrite_headers option 126
- rewriting addresses 374–388
 - at SMTP time 383–385
 - automatic 374–375
 - bang-path rewriting 384
 - child addresses 148
 - conditional 380
 - configured 375–388
 - curtailing 382
 - disabling 380
 - extended example 385–387
 - flags controlling rewriting 382–385
 - general 376–377
 - headers lines in transports 157
 - in transports 377
 - incomplete domain 375
 - lookup-driven 381
 - order of 376
 - overview 375–376
 - phrase included 382–383
 - repeating a rule 382
 - return path in transports 158
 - rule application 380
 - rule format 378–379
 - rule patterns 379–380
 - rule usage 378
 - testing rewriting rules 388
 - unqualified new recipient 382
- RFC 1413 (Identification Protocol) 462–463
 - data in log lines 517
 - disabling callback 463
 - forcing a value 486
 - logging timeout 513
- RFC conformance 466–471
- rfc1413_hosts option 463
- rfc1413_query_timeout option 463
- rmail* command 503
- root*, delivery as considered harmful 459
- root* privilege 244, 457–459
 - Exim overview 458
 - running without 459–460
 - Unix overview 457–458
- routers 122–150
 - accept** 122–123
 - routers (*continued*)
 - adding data for transports 110–113
 - adding header lines 111–113
 - automatic skipping 45
 - changing successful outcome 107–110
 - changing the return path 113
 - checking for local user 105
 - condition precondition 107
 - debugging 120
 - definition of 33
 - DNS timeout 116–117
 - dnslookup** 123–126
 - erroneous IP addresses, ignoring 109
 - fallback hosts 115–116
 - forcing verification failure 108–109
 - generic options 100–121
 - \$home* variable in 100
 - ipliteral** 127
 - list of 122
 - local part prefix/suffix 101–102
 - manualroute** 88, 127–134
 - overriding hosts in transports 172
 - preconditions 101–107
 - processing redirected address 107
 - queryprogram** 134–137
 - redirect** 137–150
 - removing header lines 111–113
 - restricting by file existence 105–106
 - restricting domains 104
 - restricting local parts 104
 - restricting senders 105
 - return values from 37
 - routing to the local host 117–119
 - setting environment for local delivery 113–115
 - skipping for EXPN 104
 - skipping when verifying 103
 - “unseen” delivery 108
 - use for verification only 103
 - use when testing 104
 - use when verifying 103
 - using transports 47–48
 - router_home_directory option 153
 - route_data option 131
 - route_list option 89, 127
 - routing
 - an address 35–37
 - by external command 134
 - complications 44–45

- routing (*continued*)
 - defer, forcing 143–144
 - DNS records 23
 - failure, forcing 143–144
 - introductory example 33
 - loops 45
 - manually 88, 127–134
 - message when unroutable 116
 - MTA overview 16–17
 - parallelism 83
 - remote address to local host 45
 - rules for **manualroute** router 127
 - same domain 124, 134
 - simple example 37–44
 - temporary errors 261
 - testing 496–497
 - to a single host 127
 - to IP addresses 127
 - to local transport by **manualroute** 132
 - using local data 88
 - using the DNS 123
 - rsmtp* command 503
 - run expansion, disabling in filters 214
 - runq* command 504
 - \$runrc* variable 436
 - runtime configuration *see* configuration
- S**
- S= in log lines 513
 - S option 490
 - same domain, routing 124, 134
 - same_domain_copy_routing option
 - in **dnslookup** router 124
 - in **manualroute** router 134
 - saslauthd* daemon 425
 - save* filter command 223–224
 - disabling 213
 - SBL (Spamhaus Block List) 2, 19
 - scanning
 - at SMTP time 357–367
 - for viruses 93–98, 357–359
 - MIME parts 362–365
 - with a local function 367
 - with regular expressions 366
 - search_parents option 125
 - security issues 456–460
 - seen filter command qualifier 211, 220
 - self option 45, 118
 - semicolon *see* ; (semicolon)
 - sender address
 - abuse of 18
 - changing 79
 - empty 13
 - for locally submitted message 60, 84, 304–305, 464, 484–485
 - from -f option 304
 - from “From ” line 304
 - in bounce messages 13
 - in MAIL command 14
 - in *Return-path:* header line 43
 - invalid 18
 - replacement by mailing list 13
 - restricting in routers 105
 - set by trusted user 304
 - testing 82
 - verifying 19, 338–339
 - Sender:* header line 464, 485
 - input processing 371–372
 - sender name in header line 485
 - senders ACL condition 337
 - senders option 81
 - \$sender_address* variable
 - in **autoreply** transport 205
 - \$sender_address_domain* variable 99
 - sender_domains ACL condition 337
 - \$sender_helo_name* variable 306
 - \$sender_host_address* variable 278
 - \$sender_host_authenticated* variable 287
 - \$sender_host_name* variable 306
 - \$sender_ident* variable 465
 - \$sender_rate* variable 342
 - \$sender_rate_limit* variable 342
 - \$sender_rate_period* variable 342
 - sender_unqualified_hosts option 305
 - Sendmail
 - command interface 2
 - command line compatibility 502–503
 - separator character in lists 59
 - serialize_hosts option 167, 243
 - serializing connections to hosts 167
 - server_condition option 290
 - server_prompts option 290
 - server_secret option 293
 - server_set_id option 290, 294
 - set ACL modifier 329
 - setuid *root* 244, 458
 - SHA-1, for password encryption 423

- shadow transports 163–164
- shadow_condition option 164
- shadow_transport option 163
- sharp sign *see* # (hash, sharp sign)
- shell
 - for *pipe* filter command 224
 - not used for pipe command 86
 - pipe** transport 198, 199
 - running Exim from 302
- Sieve filter 2
 - configuring **appendfile** for 184
 - Exim filter, compared with 208
 - redirect** options for 147
 - testing 216–218
- sieve_subaddress option 147
- sieve_useraddress option 147
- sieve_vacation_directory option 147
- SIGHUP signal 32, 51, 249, 536
- signature, digital 98
- SIGUSR1 signal 526
- simultaneous message delivery 67
- single-key lookup, definition 58
- single-quote *see* ' (single-quote)
- Size button (Exim monitor) 530
- size of messages, limiting 63, 301
- SIZE SMTP option 14, 259, 472
 - in **smtp** transport 170
 - on incoming message 296
 - with transport filter 161
- size_addition option 170
- skip_delivery log selector 242, 522
- skip_syntax_errors option 80, 149
- slash *see* / (forward slash)
- smart host 274, 461
 - definition 127
 - router configuration 128
- SmartList 83
- SMTP (Simple Mail Transfer Protocol)
 - active host name 479
 - authentication *see* authentication
 - banner strings 479
 - batched 95, 178, 179–180, 299
 - batched, use of affixes 157
 - controlling incoming connections 62–63
 - encryption 16
 - extended, avoiding use of 168
 - fixing malformed addresses 383
 - incoming from all sources 301
 - incoming from local processes 298–299, 482
 - incoming over TCP/IP 295–298
 - line terminators 471
 - outgoing timeouts 169
 - reply syntax 13
 - response codes 13
 - response codes, changing 144, 328
 - rewriting addresses 383–385
 - summary 13–15
 - temporary errors 15
 - transferring a message 14
 - use by MUA 6
 - use of SIZE option 170
- SMTP connections
 - for multiple messages 489
 - limiting 248
 - logging 515
 - reserving for certain hosts 248
- smtp** transport 165–174
 - affixes in RCPT 157
 - connection control 168–170
 - fallback hosts 173
 - hosts tried, limiting 166
 - IP address lookup 173
 - limiting connections 166
 - LMTP protocol 171
 - local host 174
 - multiple addresses 166
 - overriding router's hosts 172
 - primary list of hosts 172
 - randomizing lists of hosts 173
 - retry control 174
 - serializing connections 167
 - specifying hosts 172–174
 - use of AUTH command 170
 - use of SIZE option 170
- \$smtp_command* variable 320
- SMTPS protocol 278
- smtp_accept_max option 62, 248
- smtp_accept_max_per_host option 248
- smtp_accept_queue option 63, 248
- smtp_accept_queue_per_connection option 250, 275
- smtp_accept_reserve option 62–63, 248
- smtp_active_hostname option 247, 479
- \$smtp_active_hostname* variable 479
- smtp_banner option 479

- smtp_check_spool_space option 296
- \$smtp_command* variable 320
- \$smtp_command_argument* variable 320
- smtp_connect_backlog option 63, 249
- smtp_etrn_command option 298
- smtp_etrn_serialize option 298
- smtp_load_reserve option 62
- smtp_ratelimit_xxx options 308
- smtp_reserve_hosts option 62, 248
- \$sn0–\$sn9* variables 221
- socket
 - Internet 435
 - reading from 435
 - Unix domain 435
- Solaris
 - Bourne shell, *echo* command 288
 - file system performance 67
 - ndbm* library 393
 - pkill* command 527
 - socket-related functions 547
 - TZ variable 472
- source routed address 470
- SPA (NTLM) authentication method 295
- spam checking 16
 - case-sensitivity 455
 - in ACLs 359–362
 - using transport filter 162
- spam, collateral 18, 476
- SpamAssassin 359–362
 - specifying connections 361
- spamd* 361
- \$spam_xxx* variables 360
- split_spool_directory option 66, 240
 - with *queue_run_in_order* 253
- spool, definition of word usage 7
- spool directory
 - creation 551
 - space, checking 472–473
 - splitting 66
- “Spool file is locked” 242, 522
- SQL lookups 402–403
 - example of use of macros 55
- SQLite 402–403
- sqlite* lookup type 402–403
- square brackets *see* [] (square brackets)
- SSL *see* TLS
- SSMTP protocol 278
- standards for Internet messages 9
- starting Exim, no such concept 30
- STARTTLS SMTP command 276
- statistics, extracting from log files 523–525
- “sticky bit” 182, 553
- stopping Exim, no such concept 30
- string expansion *see* expansion
- strip_excess_angle_brackets
 - option 469
- strip_trailing_dot option 469
- Subject:* header line
 - in bounce messages 477
 - in quota warning messages 195
 - in warning messages 478
 - logging 516
- subject option 206
- submission control 368
- submission mode 330, 368
 - suppressing 330, 368
- submission protocol 7
- suffix for local part 81, 87
 - in RCPT 157
- supplementary groups 152
- suppressing
 - automatic header rewriting 126
 - delivery of messages 500
 - duplicate *syslog* lines 509
 - immediate delivery 65, 252
 - local submission processing 372
 - message logs 69, 506
 - re-expansion of mailing lists 81
 - reject log 506
 - routers during verification 103
 - Spool file is locked* 522
 - string expansion 231
 - TLS in outgoing connections 280
 - warning messages 475
- suppress_local_fixups control
 - 330, 368
- symbolic link for mailbox file 183
- synchronous delivery 461, 486
- syntax
 - errors in *.forward* files 149–150
 - errors in mailing lists 80
 - errors in redirection data 148–149
 - errors in string expansions 57
 - of options 53
- syntax_errors_text option 149
- syntax_errors_to option 80, 149
- sysadmin
 - adding to Exim group 457

- sysadmin (*continued*)
 - reading log files 457
 - syslog 506, 509–510
 - syslog_duplication option 509
 - syslog_facility option 509
 - syslog_processname option 509
 - system alias file, building DBM version 394
 - system filter 208
 - additional features 235
 - setting up 214
 - testing 216–218
 - virus scanning 96–97
 - system load 251
 - reducing Exim's activity when high 61–62
 - system_filter option 214
 - system_filter_directory_
 - transport option 214, 224
 - system_filter_file_transport
 - option 215
 - system_filter_group option 215
 - system_filter_pipe_transport
 - option 215
 - system_filter_reply_transport
 - option 215
 - system_filter_user option 215
- T**
- T= in log lines 516, 519
 - t option 302, 303, 373, 483
 - TCP/IP
 - connection from local process 250
 - incoming SMTP 295
 - reusing connections 167
 - tdb (trivial data base) 393
 - temp_errors option 201
 - testing
 - before turning on 552–553
 - callouts 497
 - command line options for 495–500
 - configuration syntax and content 495–496
 - daemon 553
 - filter 216–218
 - policy controls 497–499
 - retry rules 499
 - rewriting rules 388
 - routing 104, 496–497
 - string expansion 438
 - verification of addresses 352, 496
 - testprint filter command 229
 - text option 206
 - thawing
 - automatic 488, 534
 - by forced delivery 493
 - manual 234, 237, 493, 534
 - tidying hints databases 537–539
 - time interval option values 53
 - time taken for delivery 513
 - time zone 471
 - timeout
 - after final '.' 259
 - after MAIL command 259
 - after RCPT command 259
 - in connection attempt 258
 - in DNS black lists 334
 - in DNS while routing 116–117
 - in incoming non-SMTP message 483
 - in incoming SMTP message 482
 - in outgoing SMTP 169, 258
 - in RFC 1413 query 463
 - in transport filter 162
 - in verification callout 348
 - of retry data 269
 - ultimate for address 271
 - timeout option
 - in **pipe** transport 201
 - in **queryprogram** router 135
 - timeout_defer option 162, 201
 - timestamps 471
 - in log lines 517
 - timezone option 471
 - TLS (Transport Layer Security)
 - configuring an Exim client 280–281
 - configuring an Exim server 278–280
 - encrypted connections 276–281
 - insisting on for authentication 285
 - legacy clients 278
 - requesting client certificates 279
 - requiring for outgoing connections 280
 - SSMTP/SMTSPS protocol 278
 - suppressing in outgoing connections 280
 - temporary errors 280
 - variables that are set 279
 - tls_verify_certificates option
 - main option 279
 - tls_advertise_hosts option 278
 - tls_certificate option
 - main option 278

- tls_certificate option (*continued*)
 - smtp** transport 280
 - tls_cipher log selector 280
 - \$tls_cipher* variable 279, 285
 - tls_dhparam option 278
 - tls_peerdn log selector 280
 - \$tls_peerdn* variable 280
 - tls_privatekey option
 - main option 278
 - smtp** transport 280
 - tls_require_ciphers option 281
 - tls_tempfail_tryclear option 280
 - tls_try_verify_hosts option 279, 336
 - tls_verify_certificates option 279
 - smtp** transport 281
 - tls_verify_hosts option 279
 - To: header line 11
 - with -t 303, 483
 - to option 205
 - \$tod_bsdinbox* variable 177
 - \$tod_full* variable 211
 - top bit *see* 8-bit characters
 - translating characters in expansion 419
 - transport filters 99, 160–163
 - examples 162–163
 - for message checking 162
 - return code from 160
 - SIZE option 161
 - timeout 162
 - transport option 47, 123
 - redirect** router, must not set 137
 - transports 165–207
 - adding header lines 154–156
 - address variables 153
 - appendfile** 180–196
 - autoreply** 204–207
 - body or header only 154
 - changing the return path 158
 - current directory 152
 - data added by router 110–113
 - debugging 153
 - definition of 33
 - environment for running 151
 - filtering in 160–163
 - home directory 152
 - lmtpl** 203–204
 - message size control 154
 - options, generic 151–164
 - pipe** 196–203
 - transports (*continued*)
 - removing header lines in 154–156
 - rewriting header addresses 157, 377
 - selecting by mailbox format 186
 - shadow 163–164
 - smtp** 165–174
 - use by router 47–48
 - users and groups 152
 - transport_current_directory
 - option 115
 - transport_filter option 160
 - transport_filter_timeout option 162
 - transport_home_directory option
 - 115, 153
 - trusted users 84, 94, 464–465, 484, 485
 - defining 464
 - for BSMTP 299
 - setting message parameters 465
 - setting sender address 304, 464
 - with -bs 298
 - trusted_groups option 464
 - trusted_users option 84, 464
 - TURN SMTP command 297
 - types of MTA 8
 - TZ environment variable 472
- ## U
- U= in log lines 517
 - ultimate address timeout 271
 - umask option 200
 - underscore *see* _ (underscore)
 - Unicode 467, 558
 - uniqueness of message ID 49–50
 - :unknown: in redirection lists 144
 - unprivileged running 459–460
 - restrictions 460
 - unqualified addresses
 - from remote hosts 305–306
 - in header lines 302
 - unrouteable address, message for 116
 - “unseen” delivery from router 108
 - unseen filter command qualifier 209, 220
 - unseen option 108, 113
 - untrusted_set_sender option 465
 - Update button (Exim monitor) 532
 - upgrading Exim 555
 - uptime* command 61
 - user filter 208, 212

- user option
 - in routers 48
 - in transports 48, 152
- users
 - local in routers 105
 - multiple addresses for 86–88
 - set in routers 113–115
 - trusted 84, 94
- use_bsmtplib option
 - appendfile** transport 132, 179
 - default for message affixes 177
 - in **pipe** transport 95
 - pipe** transport 179
- use_crlf option 179
- use_fcntl_lock option 189
- use_lockfile option 189
- use_mbx_lock option 190
- use_shell option 199, 225
- /usr/lib/sendmail* 302, 553
- /usr/sbin/sendmail* 246, 302, 553
- /usr/ucb/vacation* command 177
- UTC (Universal Coordinated Time)
 - in timestamps 472
 - offset from 581
- UUCP 1
 - bang-path addressing, not supported 90
 - bang-path addressing, rewriting 384
 - delivering to 90
 - “From” line 369
- uucp_from_pattern 304
- uucp_from_sender option 304

V

- v option 217, 500
- vacation* filter command 226–228
 - disabling 214
- vacation message 204
 - filter example 209
- \$value* variable 128, 429, 433, 435, 436
- variables
 - in expanded strings 409
 - in filter 221
 - list of 566–582
 - set in message ACLs 320
 - set in MIME ACLs 362
 - set in non-message ACLs 320
 - settable in ACLs 322–323
 - testing empty 426

- verify option
 - use with **redirect** router 139
- verifying
 - addresses 346–356
 - addresses, effect of redirection 351
 - addresses, ignoring defer 346
 - addresses, testing 352
 - addresses, with callout 346–350
 - callout caching 350
 - dedicated router for 103
 - EHLO and HELO 307–308
 - forcing failure by routing 108–109
 - forward files, use for 139
 - header address, callout parameters 349
 - host names 306–307
 - recipient address, callout parameters 349
 - sender address 19, 338–339
 - sender address, callout parameters 348
 - sender address, failure details 350
 - skipping *.forward* file 103
 - skipping routers 103
 - testing 496
 - use of routers 103
- verify_only option 123
- VERP (Variable Envelope Return Paths) 158–160
- vertical bar *see* | (vertical bar)
- virtual domains 74–78
 - default recipients 76–77
 - multiple lists 74
 - postmasters 77–78
 - single list for several 76
- virus scanning
 - in ACLs 357–359
 - of accepted messages 93–98
 - on external host 97–98
 - on local host 94–96
 - using system filter 96–97
 - using transport filter 162
- VRFY SMTP command 103, 296–297

W

- wait-* databases 243
- warn verb in ACLs 322
- warning message 46
 - customizing 478
 - for delivery delay 475–476
 - for mailbox quota exceeded 195

- \$warn_message_delay* variable 478
- warn_message_file* option 478
- \$warn_message_recipients* 478
- web site 3
- weekday name, obtaining 210
- whitespace
 - after SMTP response code 13
 - at configuration line continuation 51
 - in alias continuation 39
 - in arguments for expansion operators 410
 - in command for **pipe** transport 198
 - in data for *extract* 433
 - in *errors_copy* option 474
 - in expansion strings 407
 - in filter files 218
 - in header continuation 10
 - in lists 58, 440
 - in *lsearch* files 391
 - in macro definition 54
 - in **manualroute** routing rules 127
 - in retry rules 266
 - in rewriting rules 378
- whoson* lookup type 406
- widening domains
 - by the DNS 124
 - in **dnslookup** router 125
- widen_domains* option 125
- wildcard
 - in linear search data 391, 442
 - in local part prefix/suffix 87, 102
 - in MX record 125
- wildlsearch* lookup type 391
- workstation, forwarding mail to 88–89
- write_rejectlog* option 506

X

- X= in log lines 280, 516, 519
- X Windows 50, 528

Z

- zero in DBM key string 394, 536
- “zombie” processes 249
- zones in the DNS 21–22

About the author

Philip Hazel has a Ph.D. in applied mathematics. He has been writing general-purpose software for the Computing Service at the University of Cambridge in England for over 35 years. Since moving from an IBM mainframe to Unix in the early 1990s, Philip has become more and more involved with email. He started developing Exim in 1995 and PCRE (the regular expression library) in 1997. Since then, most of his working time has been spent maintaining and extending this software.

Colophon

This first edition of this book was created on a Sun workstation running Solaris. The update for the second edition was done on a PC running Gentoo GNU/Linux. The applications software in both cases was mostly written by Philip Hazel. The NE text editor was used to create a marked-up file for processing by the SGCAL text formatting program. The figures were created in the Aspic drawing language that is integrated with SGCAL. The main output of SGCAL was converted into PostScript, at which point the EPSF screenshots were incorporated. The auxiliary output for the index and the table of contents was processed by Perl scripts to make further input that was re-processed by SGCAL. Finally, a Perl script joined the separate PostScript files together to form the complete book.

The main text of the book is set in Times fonts. The headings are set in Helvetica; the examples use Courier.

The production of the first edition of this book was sponsored by the following organizations:

- SWITCH – The Swiss Education and Research Network
- Linpro AS, Norway
- Multithread Consultants Ltd, UK
- Nova Web Hosting Ltd, UK

The author and publisher are grateful for this support from the Exim community.